

LOW-PROFILE ENTEROSTOMY DEVICE

BACKGROUND OF THE INVENTION

5 Field of The Invention: This invention relates to medical devices for use with humans and animals, and specifically relates to enterostomy devices for insertion in the stomach or intestine to provide delivery of nutrients and other substances directly to the gastrointestinal tract of patients who cannot be fed by other conventional means.

10 Statement of the Art: It frequently becomes necessary in the medical treatment of humans and animals to provide nutrients or other substances to the patient's stomach by means other than the mouth due to the existence of some condition in, or relative to, the mouth or esophagus which renders impossible the normal intake of fluids or nutrients through the mouth. Such conditions may include, for example, a localized disease condition of the mouth or esophagus or the inability of the patient to chew or swallow. Delivery of fluids or nutrients to the patient's stomach may be provided in one of three generally-recognized methods-- namely nasoenteric tube placement, gastrostomy or jejunostomy. Feeding via

15 nasoenteric tube involves the positioning of one or more tubes through the patient's nostrils, through the nasal passages to the throat and down the esophagus to the stomach. Gastrostomy involves the formation of a stoma, or opening, through the patient's abdominal wall and stomach, followed by placement of a tube through the stoma for delivery of fluids and nutrients directly to the stomach. Jejunostomy

20 involves the formation of a stoma through the lower abdominal wall and the intestine, followed by the insertion of a tube through the stoma and into the intestinal tract.

25 Each type of feeding identified above has its appropriate applications and contraindications. For example, nasoenteric tube insertion is suitable for temporary or short term feeding requirements, but is unsuitable where the patient cannot

30

tolerate the placement of such tubes or where feeding must be continued for longer than a week or two. Gastrostomy is appropriate for longer periods of required feeding (e.g., more than four weeks) and has the particular advantage of using the stomach's storage capacity, osmotic regulation and prolongation of intestinal transit to maximize the intake of nutrients. Gastrostomy, however, may not be suitable where the stomach is in a diseased condition, where there is abnormal gastric emptying, significant esophageal reflux or lack of inherent gag reflex in the patient. Jejunostomy is appropriate where gastrostomy is contraindicated by one of the aforementioned conditions, but is less desirable than gastrostomy because of the shortened period of time that the nutrients may be absorbed by the intestinal tract.

A number of gastrostomy and jejunostomy devices have been developed over the years to supply a fluid-communications port to the stomach or intestine. Examples of gastrostomy and jejunostomy devices are disclosed in U.S. Patent No. 5,549,657 to Stern, et al.; U.S. Patent No. 5,411,491 to Goldhardt, et al.; U.S. Patent No. 5,391,159 to Hirsch, et al.; U.S. Patent No. 5,356,391 to Stewart; U. S. Patent No. 5,342,321 to Potter; U.S. Patent No. 5,336,203 to Goldhardt, et al.; U.S. Patent No. 5,080,650 to Hirsch, et al.; U.S. Patent No. 4,861,334 to Nawaz; U.S. Patent No. 4,850,953 to Haber, et al., and U.S. Patent No. 3,915,171 to Shermata.

Previously disclosed enterostomy devices are generally configured in a similar manner to deliver nutrients to the stomach or intestine. Specifically, they comprise a tube which is positionable through a stoma or opening formed through the patient's abdominal wall and stomach or intestine, a retainer device positioned at one end of the tube which is located within the stomach or intestine, and a valve device positioned at the end of the tube opposite the retainer device. The valve device provides at least one opening through which fluid can be introduced to flow through the tube. The valve device may also serve to maintain the tube in position within the stoma and often provides a means by which the tube may later be removed from the stoma.

The retainer devices of previously disclosed gastrostomy devices generally

function well for their intended purpose (i.e., anchoring the gastrostomy device to the stomach or intestinal lining and delivery of substances to the gastrointestinal tract), but they are almost uniformly rendered disadvantageous in being large or potentially obstructive in configuration. That is, the design or configuration of the retainer device of most known gastrostomy devices is such that it extends a significant distance into the lumen of the stomach or intestine, thereby causing an obstruction of the stomach or intestine, or the retention device extends so far into the stomach or intestine that it contacts tissue on the opposing side of the stomach or intestine causing irritation or infection. Further, the configuration of some known devices provides an insufficient surface area for contact with the stomach or intestine lining, which can result in dislodgement and accidental removal or expulsion of the gastrostomy device from the patient's body. Additionally, most gastrostomy devices provide an aperture, in axial alignment with the feed tube of the device, through which nutrients are feed and, oftentimes, through which fluids are vented from the stomach or intestine. To prevent entry of infectious agents or accidental release of fluids from the stomach or intestine through the gastrostomy device, many known devices provide a tethered plug which can be inserted into the aperture. In such devices, trauma to the stoma occurs when a syringe or tube set is inserted in the axially-aligned aperture and trauma also occurs to the stoma when the plug is inserted and removed from the aperture.

Thus, it would be advantageous to provide an enterostomy device which is structured to provide a retaining member having an increased area of contact with the stomach or intestinal lining, thereby preventing premature or unintended release of the device from the patient, and one which is unobstructive in configuration to prevent blockage in the stomach or intestine. It would further be advantageous to provide a enterostomy device which is structured with a low-profile valved hub which eliminates trauma imposed on the stoma as is typically experienced with known gastrostomy devices.

SUMMARY OF THE INVENTION

In accordance with the present invention, an enterostomy device is configured to provide a low-profile retaining member positionable within the stomach or intestine of a patient to prevent obstruction of the patient's gastrointestinal tract while providing sufficient contact between the retaining member and the gastrointestinal tract to prevent dislodgement of the device from the patient. The enterostomy device of the present invention is also structured with a port hub having a low profile to facilitate inflation of the retention member, feeding through the gastrostomy device and venting of fluids through the gastrostomy device while preventing trauma to the stoma. The enterostomy device is structured to be easily deployable through an existing stoma and provides an inflatable retaining member which is easily deployed within the stomach or intestine. The enterostomy device of the present invention is suitable for use with both human and animal patients, but is described herein with respect to use in humans as one exemplar application.

The enterostomy device of the present invention is adaptable for use as either a gastrostomy device or a jejunostomy device. In either application, the enterostomy device comprises a stoma tube having a first end positionable toward the outside of the patient's body (also referred to as the proximal end) and a second end positionable within the patient's body (also referred to as the distal end). At least one opening is generally located at the first, or proximal end, of the stoma tube which enables the introduction of fluid or other substances into the stoma tube. A low-profile retaining member is located at the second, or distal, end of the stoma tube and is positionable within the patient's body. The retaining member is generally structured with an increased surface area for contacting the lining of the stomach or intestine to assure that the enterostomy device cannot be accidentally removed.

The retaining member is generally structured as a flattened inflatable ring which extends outward from the stoma tube at the distal end thereof. The flattened profile of the retaining member and the distance it extends from the stoma tube provide an increased surface area for contacting the stomach or intestinal lining

about the stoma to thereby prevent accidental dislodgement or removal of the enterostomy device from the stoma. The inflatable ring of the retaining member is in fluid communication with an inflation line incorporated into the stoma tube and is structured to receive a fluid, either gas or liquid, from the inflation line to inflate the ring. For example, the stoma tube may be structured with a valved chamber through which an inflation fluid is injectable to inflate the ring. Upon inflation, the inflatable ring extends outward from the distal end of the stoma tube in an plane generally perpendicular to the longitudinal axis of the stoma tube. The retaining member is made of a biocompatible, flexible material, such as silicone or other suitable material, and is configured to prevent incorporation of the device into the surrounding stomach or intestinal lining.

The port hub located at the proximal end of the stoma tube is configured to be located on the outside of the patient's body and effectively encloses or covers the stoma to prevent leakage or infiltration of foreign matter through the stoma opening. The port hub also functions to provide means for ingress and egress of fluids through the stoma tube and is preferably structured with a means for closing off the stoma tube to thereby prevent the infiltration of unwanted matter or the escape of fluids through the stoma tube. The port hub is preferably configured to have a low profile as well, and is configured to rest against the patient's body in an unobtrusive manner so as not to be readily detectable under clothing. The configuration of the port hub may vary considerably, but is structured with at least one port through which substantially flowable fluids or nutrients can be introduced for delivery to the stomach or intestine via the stoma tube. In a preferred embodiment of the invention, the port hub includes at least one port through which a fluid or other substance may be injected. The axis of the port may generally be oriented normal to the axis of the stoma tube and may be placed in fluid communication therewith.

In one particularly preferred embodiment, the port hub is configured with a single port and is structured to be rotatable relative to the stoma tube so that the port can be selectively aligned with one or more openings leading into the stoma tube.

The rotatable port hub can also be rotated to disengage the port from alignment with the opening or openings to the stoma tube to place the enterostomy device in a closed position. The configuration thus eliminates the need for tethered plugs. Furthermore, because the opening or openings into the stoma tube are normal (i.e., perpendicular) to the axis of the stoma tube, no pressure is applied to the axis of the stoma tube, as in prior devices, to cause trauma to the stoma. The rotatable port hub is particularly structured to provide easy access to the inflation line for inflating the retaining member and to access the port for feeding or venting through the stoma tube, and the design eliminates the need for bulky tube sets as are typically required with known gastrostomy devices, although the present invention is structured for accepting a tube set arrangement if desired.

In one embodiment, the enterostomy device of the present invention may be configured for use as a gastrostomy device for implantation through an existing stoma and into a patient's stomach. The gastrostomy device provides a low-profile retaining member positionable against the stomach wall to prevent obstruction of the interior of the stomach. In an alternative embodiment, the enterostomy device may be configured for use as a jejunostomy device for implantation through an existing stoma into a portion of the intestine. The jejunostomy device is structured to provide a low-profile retaining member positionable within the intestine which does not obstruct the interior of the intestine. Thus, materials may flow through the intestine and past the retaining member without being obstructed thereby. The jejunostomy device further includes a jejunostomy tube which extends from the distal end of the stoma tube to deliver fluids or other substances into the intestine.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which illustrate what is currently considered to be the best mode for carrying out the invention:

FIG. 1 is a perspective view of the enterostomy device of the present invention, prior to deployment in a pre-existing stoma, illustrating the inflation line and

rotatable port hub;

FIG. 2 is a perspective view of the enterostomy device shown in FIG. 1, rotated 180° to illustrate the port of the port hub;

FIG. 3 is a view in lateral cross section of the enterostomy device shown in FIG. 1, taken at line 2-2, illustrating the rotatable port hub in a closed position;

FIG. 4 is a view in lateral cross section of the enterostomy device shown in FIG. 1, taken at line 2-2, illustrating the port aligned with an inlet opening of the stoma tube;

FIG. 5 is a view in lateral cross section of the enterostomy device shown in FIG. 1, taken at line 2-2, illustrating the port aligned with an outlet opening of the stoma tube;

FIG. 6 is a view in longitudinal cross section of the enterostomy device shown in FIG. 1, taken at line 3-3, illustrating the rotatable port hub in a closed position and the retaining member in a pre-deployed orientation;

FIG. 7 is a view in longitudinal cross section of the enterostomy device shown in FIG. 1 where the rotatable port hub is aligned with the inlet opening and the retaining member is in a pre-deployment orientation;

FIG. 8 is a view in lateral cross section of the enterostomy device illustrating the retaining member in a partially deployed position;

FIG. 9 is a view in lateral cross section of the enterostomy device illustrating the retaining member in a fully deployed position;

FIG. 10 is a view in lateral cross section of the present invention illustrating an alternative embodiment of the retaining member;

FIG. 11 is a view in lateral cross section of the present invention illustrating another alternative embodiment of the retaining member;

FIG. 12A is a view in partial cross section illustrating initial insertion of the enterostomy device of the present invention into a pre-existing stoma;

FIG. 12B is a view in partial cross section illustrating partial deployment of the enterostomy device, in the form of a gastrostomy device, in a patient's abdomen;

FIG. 12C is a view in partial cut away illustrating full deployment of the enterostomy device in a patient's abdomen;

FIG. 13 is a view in partial cross section illustrating an alternative embodiment of the enterostomy device of the present invention configured for use as a jejunostomy device and being partially deployed in a patient's intestinal tract; and

FIG. 14 is a view in partial cross section of the jejunostomy device illustrated in FIG. 13 as it may appear upon full deployment within the intestinal tract of a patient.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The general configuration of the enterostomy device 10 of the present invention is illustrated in FIGS. 1-7, where FIGS. 1 and 2 illustrate the device 10 in a pre-deployment mode. Further, FIGS. 1-11 illustrate the device 10 as it may be configured for use as a gastrostomy device 20 positionable within the stomach of a patient while FIGS. 13 and 14 illustrate the present invention as a jejunostomy device.

Referring to FIGS. 1 and 2, the gastrostomy device 20 generally comprises a stoma tube 22 having a first end 24, also referred to as the proximal end, positionable toward the outside of the patient's body and a second end 26, also referred to as the distal end, which is positionable within the patient's stomach. The circumferential and length dimensions of the stoma tube 22 may vary and are dictated by the length and inner diameter of the existing stoma formed through the patient's body. Therefore, in a medical setting, a gastrostomy device having the appropriate circumferential and length dimensions suitable for use with the given patient would be selected from an inventory of variably sized gastrostomy devices of the present invention.

As generally shown in FIGS. 1 and 2, a rotatable port hub 28 is located at the first end 24 of the stoma tube 22 to facilitate access to the stoma tube through a port 30 formed in the rotatable port hub 28. The rotatable port hub 28 is also configured

to accommodate a valved inflation connector 32 which is formed with the stoma tube 22, as illustrated and described more fully below. The rotatable port hub 28 is rotatable by a handle 34 generally formed at the top of the rotatable port hub 28 and is configured with a slot 36 which permits rotation of the port hub 28 relative to the stoma tube 22 and the fixed inflation connector 32 of the stoma tube 22.. As also shown generally in FIGS. 1 and 2, an inflatable retaining member 40 is located at the distal end 26 of the stoma tube 22 and extends outward therefrom.

As shown and described more fully with reference to FIGS. 3-7, the stoma tube 22 has a central bore 42, formed about a central axis 44 (FIG. 6), which extends from the first end 24 to the second end 26 of the stoma tube 22. The first end 24 of the stoma tube 22 may be formed with an outward-extending flange 46 about which the rotatable port hub 28 is positioned and movable. As shown in FIG. 6, the inflation connector 32 is formed through the flange 46 of the stoma tube 22 and is in fluid communication with an inflation line 48 which extends through the wall 50 of the stoma tube 22. The inflation line 48 may be co-extensive, as shown, with the central bore 42 of the stoma tube 22 and is in fluid communication with the retaining member 40, shown inserted within the central bore 42 of the stoma tube 22 in a pre-deployment mode. The inflation connector 32 is structured in a conventional manner known in the art where a valve permits introduction of an inflation fluid, such as air or saline solution, through the valve and into the inflation line 48 for inflation of the retaining member 40. Any suitable valve structure may be employed in the inflation connector which retains the inflation fluid within the retaining member 40 until such time as the inflation fluid may be released from the retaining member 40 through the inflation line 48. Such devices are commonly known in the art and are not described further here.

As shown more fully in FIGS. 3-5, the rotatable port hub 28 may be selectively rotated relative to the flange 46 of the stoma tube 22 to align the port 30 with one or more openings formed through the flange 46 or to close the gastrostomy device 20 so that the central bore 42 is inaccessible from outside the body of the patient. That is,

as shown in FIGS. 3-5, for example, two openings, comprising an inlet 56 and an outlet 58, may be formed through the flange 46 of the stoma tube 22, each having an axis 60, 62, respectively (FIG. 3), which is substantially perpendicular to the central axis 46 of the central bore 42. By "substantially perpendicular" is meant that the axis 60, 62 of one or both of the respective inlet 56 and outlet 58 may be angled upwardly relative to the central axis 44 of the stoma tube 22 and may, therefore, not be strictly perpendicular thereto. As shown in FIG. 3, the port hub 28 may be rotated so that the port 30 is not aligned with either the inlet 56 or the outlet 58 so that access to the central bore 42 is prevented. In such a position, the gastrostomy device 20 may be said to be in a closed position.

As shown in FIGS. 4 and 7, the port hub 28 may be rotated relative to the stoma tube 22 to align the port 30 with the inlet 56 to thereby gain access to the central bore 42 of the stoma tube 22 for feeding the patient. The inlet 56 may preferably be configured with a valve 64, such as a one-way valve, which enables material to be introduced into the inlet without reflux of material out of the inlet. The valve 64 may, for example, be openable by the insertion of a male Luer connector into the port 30 through which the feeding material flows to the central bore 42. Rotation of the port hub 28 relative to the flange 46 of the stoma tube 22 and the fixed inflation connector 32 is accomplished by formation of a slot 36 in the rotatable port hub 28 through which the inflation connector 32 extends, as shown. It should be noted that the inflation connector 32 may be configured to extend a distance beyond the circumference of the port hub 28 to provide a graspable element which may be held while turning the handle 34 of the port hub 28 to assure stability of the stoma tube 22 during rotation of the port hub 28.

As shown in FIG. 5, the port hub 28 may also be rotated to align the port 30 with the outlet 58 for venting fluids, such as gas, from the patient's stomach. The outlet 58 may preferably be structured with a valve 66, such as a one-way valve, which allows fluids to escape from the stomach cavity, but does not allow matter from the environment external to the stomach to enter into, and possibly infect, the

stomach. The valve 66 may, most suitably, be operable as a result of pressure differentials existing between the internal and external gastrointestinal environment. Obviously, when the port 30 is not aligned with the outlet 58, venting cannot occur. It should be noted that while simple flapper valves are shown representationally in
5 FIGS. 3-5 and 7 as means for controlling the flow of fluids or other material into and out of the inlet 56 and outlet 58, respectively, any number of suitable valving devices may be employed to achieve the desired function, including, for example, ball valves or the like. Again, it can be seen in FIG. 5 that the existence of the slot 36 formed in the rotatable port hub 28 allows movement of the port hub 28 relative to the fixed
10 inflation connector 32 formed in the flange 46 of the stoma tube 22.

FIG. 6 illustrates, in one exemplar embodiment of the invention, how the retaining member 40 is located within the central bore 42 of the stoma tube 22 prior to deployment of the gastrostomy device 20 in the patient's stomach. FIG. 8 further illustrates how the retaining member 40 may be deployed from the stoma tube 22 by
5 introduction of an inflation fluid, represented by arrow 70, through the inflation connector 32 and the inflation line 48. As the inflation fluid enters the retaining member 40, it is forced out of the central bore 42 of the stoma tube 22 until, as shown in FIG. 9, the retaining member 40 is fully deployed.

FIG. 9 illustrates one exemplar configuration of the retaining member 40
20 comprising a tubular ring 72 distanced from the distal end 26 of the stoma tube 22 by a skirt 74 of flexible material. The retaining member 40 of the illustrated embodiment provides a low-profile, or flattened ring, configuration which effectively prevents obstruction of the stomach by the retaining member 40, as is frequently experienced with prior devices. Furthermore, it can be seen that the retaining
25 member 40 essentially forms the distal end of the gastrostomy device 20 since the stoma tube 22 does not extend beyond the retaining member 40 as is typically the case in prior devices and, therefore, the retaining member 40 prevents the distal end 26 of the stoma tube 22 from contacting the stomach lining and causing irritation or infection. Additionally, the flattened configuration of the retaining member 40 and

the distance 78 with which it extends outward from the stoma tube 22 provide increased surface area for contacting the stomach lining to thereby prevent dislodgement or accidental release of the gastrostomy device 20 from the stoma formed through the patient's body.

Alternative embodiments of the retaining member 40 which provide a similar flattened configuration with increased surface area are shown in FIGS. 10 and 11. In FIG. 10, the retaining member 40 is formed as a flattened toroidal ring 80 which encircles the distal end 26 of the stoma tube 22. The flattened ring 80 is filled with fluid (i.e., gas or liquid) through the inflation line 48 as previously described and provides a flattened top surface 82 for contacting against the stomach lining of the patient. The extension of the flattened ring 80 from the stoma tube 22 ensures that the gastrostomy device will not become dislodged from the stoma formed through the patient. Similarly, FIG. 11 illustrates another alternative embodiment of the retaining member 40 comprising a toroidal ring 84 of less flattened dimension, but which still provides increased surface area for contacting the stomach lining. The toroidal ring 84 of the illustrated embodiment is distanced from the stoma tube 22 by an inflated collar 86 of flexible material.

The retaining member 40 of the present invention is preferably made from a flexible, biocompatible material, such as silicone or other suitable material, which not only enables the retaining member 40 to be collapsed to a smaller dimension for positioning within the stoma tube 22 prior to deployment, but renders the retaining member 40 compatible to the environment of the stomach. By its architecture and composition, the retaining member 40 prevents epithelialization or similar attempts by the body to incorporate the retaining member 40 into the surrounding tissue. Incorporation is principally prevented as a result of the rounded configuration of the inflatable ring 72 (FIG. 9) or toroidal ring 84 (FIGS. 10 and 11) of the retaining member 40.

FIGS. 12A, 12B and 12C illustrate the sequential steps of inserting and deploying the gastrostomy device 20 of the present invention in the stomach of a

patient. Deployment is initiated by providing the gastrostomy device 20 in a pre-deployment mode, as previously described and illustrated in FIGS. 1-11. The stoma tube 22 is positioned through an existing stoma 100 formed through the abdominal wall 102 of a patient, as illustrated in FIG. 12A. Because the present invention is
5 designed for insertion in a pre-existing stoma, and because the formation of a stoma is a well-known procedure in the medical arts, the process for forming a stoma will not be discussed herein. The stoma tube 22 is inserted through the stoma 100 until the distal end 26 of the stoma tube 22 is within the environment of the patient's stomach 104. A fluid delivery device 106, such as a syringe, is positioned within the
10 inflation connector to open the valving mechanism therein, and a fluid, such as a gas or saline liquid, is injected into the inflation line 48 of the stoma tube 22. As the fluid moves through the inflation line 48, the retaining member 40 is forced out of the central bore 42 of the stoma tube 22 and into the environment of the stomach 104, as illustrated in FIG. 12B.

When sufficient fluid pressure is achieved to inflate the retaining member 40,
15 as illustrated in FIG. 12C, the fluid delivery device 106 is withdrawn from the inflation connector 32 thereby disabling the valving mechanism and maintaining fluid pressure within the retaining member 40. It can be seen from FIG. 12C that a contact surface area 108 is defined by the skirt 74 and inflated ring 72 of the retaining member 40 which contacts the lining 110 of the stomach to anchor the
20 gastrostomy device 20 in place. It can also be seen that the configuration of the retaining member 40 provides a low-profile which does not obtrusively extend into the interior of the stomach 104 as prior devices do. It can also be seen that the retaining member 40 flexibly conforms to the curvature of the stomach 104 while still
25 maintaining a generally perpendicular orientation to the axis of the stoma tube 22. FIG. 12C illustrates the gastrostomy device in full deployment within the stomach 104, ready for injection of fluids or nutrients through the central bore 42 of the stoma tube 22 and into the stomach, although the port 30 is shown in a closed position.

The enterostomy device 10 of the present invention may also be configured for use as a jejunostomy device 120, as illustrated in FIGS. 13 and 14, which illustrates deployment of the jejunostomy device 120 into the intestine 122 of a patient. As illustrated more particularly in FIG. 13, the jejunostomy device 120 of the present invention is comprised of a stoma tube 22, a rotatable port hub 28 and a retaining member 40 as previously described with respect to the gastrostomy device illustrated in FIGS. 1-11. Similarly, the retaining member 40 is housed within the stoma tube 22 prior to deployment. However, the jejunostomy device 120 also includes a jejunostomy tube 126 which, as suggested by the broken lines of FIG. 13, is housed within the stoma tube 22, along with the retaining member 40, prior to deployment.

Deployment of the jejunostomy device 120 proceeds as previously described with respect to the gastrostomy device, including introduction of an inflation fluid through the inflation connector 32 via a fluid delivery device 106, such as a syringe, to promote inflation of the retaining member 40. During deployment of the retaining member 40, the jejunostomy tube 126 may remain housed within the stoma tube 22. Once the retaining member 40 is fully deployed, the jejunostomy tube 126 may be deployed by injecting a bolus of fluid, such as saline solution, through the port 30 and into the inlet 56 to produce sufficient fluid pressure in the central bore 42 of the stoma tube 22 to eject the jejunostomy tube 126 into the intestine 122. The jejunostomy tube 126 is intended to project downstream into the intestinal tract and provides fluids and nutrients to the intestine.

The enterostomy device of the present invention is configured to provide a low-profile retaining member which, when deployed in the stomach or intestine, does not obstruct the internal space or environment thereof. The retaining member is also structured with sufficient contact surface area to prevent accidental removal or release of the enterostomy device from the stoma, but is flexible enough, when deflated, to easily remove the device from the patient. The enterostomy device of the present invention is also configured with a low-profile port hub which provides access to the stoma tube without the need for bulky tube sets, and without trauma to the

stoma formed in the patient. The structure and configuration of the enterostomy device may be varied to provide a gastrostomy or a jejunostomy device, and may be configured in number of ways to achieve the stated objectives of providing fluids and nutrients to the stomach or intestine of the patient, and venting of the stomach or intestine. Hence, reference herein to specific details of the illustrated embodiments is by way of example and not by way of limitation. It will be apparent to those skilled in the art that many additions, deletions and modifications to the illustrated embodiments of the invention may be made without departing from the spirit and scope of the invention as defined by the following claims.

5

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
22